

CleaRinse Portable Wash Down Systems

For Vessels 65' LOA and larger

Part Number 76000 5,000 GALLON SYSTEM

Measurements 37" high x 9" wide x 6" deep

Construction CNC Machined Starboard® top and base
Machined 6463 BDA Aluminum Schedule 40 Pipe
Machined Brass Fittings
Stainless Steel Screws
#10 housing w/relief valve
Glass wound poly tank
High Speed, High Flow Cation softening resin

Performance Filters and softens 5,000 gallons of dock water. Pre-filter removes chlorine and sediment from water before being softened. Large softening tank removes calcium, magnesium, tannins and other finish damaging minerals. Softening capacity is based on 5 grains of hardness. Harder water will reduce capacity. Refer to the following chart for guidance

Hardness in Grains	Estimated Capacity in Gallons
5	5,040 gallons
8	3,125 gallons
10	2,520 gallons

Well water or water containing iron will greatly affect softening capacity – often by as much as 2/3.

Maintenance When the system reaches capacity, it must be recharged using water softening salt (yellow bags). Recharging the system takes approximately 30 minutes using the supplied recharge canister.

Monthly replacement of pre-filter is required. Only Matrix 10 Micron CTO is recommended for optimal performance. Swobbit Products stocks this particular filter

Options GPI Digital water meter assembly. Accurately monitors water usage. Dual monitoring for cumulative - resets at 10,000 gallons and daily or monthly monitoring.

Warranty 5 Year Manufacturer's Warranty on Tank (only) 1 year on GPI digital meter
90 days against manufacturer's defects

Price 76000 5,000 gallon system \$955.00
76100 5,000 gallon system with GPI meter \$1,155.00
75090 10 Micron CTO Pre-filter cartridge \$18.00 each